

ATLAS KOMPAKT

Electric Driven Scissor Scissor-type
Aerial Work Platform

ACSL1212DC

Dimension

 www.atlas-kompakt.com

Working height*	12 m
A Platform height maximum	10 m
B Platform height (stowed)	1.36 m
C Platform length	2.27 m
Slide-out platform extension deck	0.9 m
D Platform width	1.15 m
E Stowed height (rails up)	2.49 m
Stowed height (rails down)	1.95 m
F Overall length	2.47 m
G Overall width	1.17 m
H Wheelbase	1.87 m
I Ground clearance (stowed)	0.11 m
J Ground clearance (raised)	0.02 m

Performance

Lift capacity	320 kg
Lift capacity (extension deck)	113 kg
Max. platform occupancy	2
Drive speed (stowed)	4.0 km/h
Drive speed (elevated)	0.8 km/h
Turning radius (inside)	0 m
Turning radius (outside)	2.2 m
Raise / lower speed	55 s / 38 s
Gradeability**	30%
Max. allowable working angle (lateral / longitudinal)	1.5° / 3°
Controls	Proportional
Wheel driver	DC motor front drive
Multiple disc brakes	Dual front wheel
Tires	381 mm x 127 mm
Battery	4x6V / 240 Ah
Charger	24V / 30 A
Weight	2950 kg

* Working height is equal to Platform height plus 2 m.

** Climbing ability is suitable for driving on slopes; Refer to Operator Manual for slope level.



Stedinger Straße 324, 27751 Delmenhorst, Germany

Electric Driven Scissor Scissor-type Aerial Work Platform

ACSL1212DC



*Electric Driving
Motor*



Standard features

- Proportional control
- Solid tire
- Horn
- Pothole protection device
- Tilt sensor with alarm
- Extended platform
- Hour meter
- Flashing beacon
- Emergency descent system
- Charging protection system
- Folding guardrails platform
- Standard transport forklift hole
- Action beep
- Emergency stop button
- Fault diagnosis system
- Self-lock gate on platform
- Safety maintenance support rod
- DC motor drive
- Automatic brakes system
- Maintenance-free battery