

ATLAS KOMPAKT

Electric Driven Scissor Scissor-type
Aerial Work Platform

ACSL0807DC

 www.atlas-kompakt.com

Dimension


Working height*	8 m
A Platform height maximum	6 m
B Platform height (stowed)	1.05 m
C Platform length	1.7 m
Slide-out platform extension deck	0.9 m
D Platform width	0.74 m
E Stowed height (rails up)	2.17 m
Stowed height (rails down)	1.79 m
F Overall length	1.86 m
G Overall width	0.76 m
H Wheelbase	1.38 m
I Ground clearance (stowed)	0.083 m
J Ground clearance (raised)	0.02 m

Performance

Lift capacity	230 kg
Lift capacity (extension deck)	113 kg
Max. platform occupancy	2
Drive speed (stowed)	4.5 km/h
Drive speed (elevated)	0.8 km/h
Turning radius (inside)	0 m
Turning radius (outside)	1.67 m
Raise / lower speed	20 s / 27 s
Gradeability**	25%
Max. allowable working angle (lateral / longitudinal)	1.5° / 3°
Controls	Proportional
Wheel driver	DC motor front drive
Multiple disc brakes	Dual front wheel
Tires	323 mm x 100 mm
Battery	4x6V / 210 Ah
Charger	24V / 30 A
Weight	1545 kg

* Working height is equal to Platform height plus 2 m.

** Climbing ability is suitable for driving on slopes; Refer to Operator Manual for slope level.



Stedinger Straße 324, 27751 Delmenhorst, Germany

Electric Driven Scissor Scissor-type Aerial Work Platform

ACSL0807DC



*Electric Driving
Motor*



Standard features

- Proportional control
- Solid tire
- Horn
- Pothole protection device
- Tilt sensor with alarm
- Extended platform
- Hour meter
- Flashing beacon
- Emergency descent system
- Charging protection system
- Folding guardrails platform
- Standard transport forklift hole
- Action beep
- Emergency stop button
- Fault diagnosis system
- Self-lock gate on platform
- Safety maintenance support rod
- DC motor drive
- Automatic brakes system
- Maintenance-free battery